

FAST FULL COLOR ENVELOPES, CARDS AND SHEETS



Print envelopes to 13" x 17"

Print up to 3,300 full color #10 envelopes per hour, 500,000+ per month



Sheets up to 13" x 22"

Average consumable cost per full color #10 envelope is only 2¢

Card stock to 14pt

Feeder holds up to 800 envelopes



Variable data at full speed

OR
4000 sheets of 20lb bond

Secap COLOR DIGITAL PRINTER +



The Secap Color Digital Printer is the new cost effective solution for printing on-demand, full color envelopes, cards, and sheets. The high capacity feeder holds up to 800 #10 envelopes / window envelopes / large envelopes (to 13"x17"), or 4000 sheets of 20lb bond. You can also print full color cards (to 14pt / 307gsm), sheets (to 13" x 22") and personalized mailing pieces running variable data at full speed.

PH: 1.800.523.0320 / 610.825.6205 www.secap.com



SECAP Color Digital Printer +

Print Method:

Electrophotographic, single pass, digital envelope press

Print Speed*:

From the paper cassette
Color: up to 36 ppm
Monochrome: up to 40 ppm
Envelope Feeder, 60 envelopes

Warm-up Time:

Up to 85 seconds

First Page Output Time:

Color: 10.5 seconds from an idle, ready state on plain paper
Monochrome: 9 seconds from an idle, ready state on plain paper

Resolution:

600 x 1200 dpi

Recommended Duty Cycle:

150,000 prints per month maximum (industry standard letter/A4 at 5%). 500,000 prints per month # 10 envelopes

HARDWARE AND SOFTWARE CAPABILITIES

Processor Type:

PowerPC 750FX, 800 MHz

Memory:

1 GB standard

Operating System Compatibility:

Windows: Windows® XP Professional, XP Home, 2003 Server;
Windows 98, 98 SE, ME, NT® 4.0 Workstation, NT 4.0 Server
(SP6 or later), 2000 Workstation (SP3 or later), 2000 Professional
(SP3 or later), 2000 Server (SP3 or later), 2000 Advanced
Server (SP3 or later); Citrix® MetaFrame® – Windows 2000
Server (ServicePack4) with Citrix MetaFrame XP® Presentation
Server Feature Release 3, Windows Server 2003 Standard
Edition with Citrix MetaFrame XP Presentation Server Feature
Release 3; Macintosh: Mac® OS 9.x, Mac OS 10.2.4 – 10.4.2;
Unix/Linux

Printer Languages:

Adobe PostScript 3, PDF v.1.4 Emulations: PCL®5c, PCL 6,
IBM PPR, EPSON FXDirect PDF Printing (Windows
environment only)

Printer Management:

Printer Drivers, Color Correct Utility, Color Swatch Utility, PDF
Direct Print, Profile Assistant, PS Gamma Adjuster, Storage Device
Manager, Admin Manager/Quick Setup, LPR Utility, Network
Printer Status

INTERFACE SUPPORT

Standard:

10/100-TX Ethernet, High-speed USB v2.0, Parallel

Ethernet Protocols:

TCP/IP, Network and Ethertalk. TCP/IP includes ARP, IP, ICMP,
TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SNMP,
DNS, SSL/TLS, JetDirect protocols; Netware includes 3.x, 4.x,
5.x, and 6.x with full NDS and NDPS support – PServer, RPrinter,
NDPS supported via dedicated NDPS Gateway. EtherTalk: ELAP,
AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP.

PAPER HANDLING

Standard Paper Input:

530 sheets (lower paper tray)

Envelope Input Feeder:

800 #10 envelopes (4.125" x 9.5" or 105 mm x 242 mm)
Min: 5.125" x 4.125" or 130.2 mm x 104.8 mm (WxH)
Max: 13" x 17" or 330.2 mm x 431.8 mm (W x H)

Delivery Stacker:

Variable speed conveyer belt

Paper Sizes Supported:

Tabloid extra (12" x 18"), tabloid, legal, letter, executive,
index cards, A3, A3 wide, A3, A4, A5, A6, B4, B5, C5

Paper Weights :

Envelopes
Trays 1: 75-216 gsm; 50 lb. text to 80 lb. cover

Print Media:

Plain paper, letterhead, glossy stock, coated, uncoated

PHYSICAL

Type:

Digital envelope press with internal Adobe PostScript controller

Dimensions (WxDxH):

including delivery conveyer
92" x 24.4" x 18.2" (233 cm x 62.0 cm x 46.2 cm)

Weight:

152 lb. (69.0 kg) without options

ELECTRICAL

Power Requirements:

120 (110 – 127) VAC; 60 Hz ± 2 Hz; 230 (220 – 240) VAC;
50 Hz, ±2 Hz

Power Consumption:

Operating: 750W
Standby: 200W
Power Save Mode: 55W

ENVIRONMENTAL

Temperature Requirements:

Operating: 50-90° F (10-32° C)
Non-operating: 32-110° F (0-43° C)
Best Print Quality: 63-80° F (17-26° C)

Humidity:

Operating: 20-80% RH
Non-operating: 10-90% RH
Best Print Quality: 50-70% RH

Noise Levels:

Operating: 53 dB
Standby: 40 dB
Power Save Mode: 40 dB

CONSUMABLES

In-Box Cartridges:

Printer ships with one each cyan, magenta, yellow and black toner cartridge;
cyan, magenta, yellow and black image drum; waste toner box, fuser unit,
and transfer belt

TYPEFACES

136 Adobe PostScript Type 1 typefaces, 86 scalable PCL fonts,
1 bitmap font, 10 TrueType® fonts, OCR A/B, USPS Barcode

* Print speed varies depending on system
configuration, software application,
driver, thickness of stock and
document complexity. Specifications
subject to change without notice.



10 Clipper Road
W. Conshohocken, PA 19428-2721
800.523.0320 • 610.825.6205
www.secap.com

Available from your authorized Secap dealer.

Bullfrog Enterprises
1581 South A Street
Springfield, OR 97477
www.bullfrogenterprises.com

© Xante, Symphony Workflow, SpeedSetter, KoolKolor, KoolToning, StripRITE, PerfectBLEND, AdvancedScan, RasterView, TrapZone, ImagerQ Concerto, VM, Harmony Violet Metal Plates, Harmony Violet CTP Developer, Harmony Violet CTP Replenisher, Harmony Litho Processor Cleaner, and Harmony Litho CTP Gum are trademarks or registered trademarks of Xanté Corporation. Adobe, PostScript 3, APPE and Accurate Screens are registered trademarks of Adobe Systems, Incorporated, which may be registered in certain jurisdictions. Fiery is a registered trademark of EFI. All other trademarks or registered trademarks are the property of their respective owners. Prices and equipment specifications subject to change without notice.

This brochure was printed on the SECAP Color Digital Printer.

REV: 05/1409

